

150 CFM

ReVent Ventilation Fan

Model - RVS150



Performance - High airflow 150 CFM, low sound 1.3 sone

ReVent with LED Lighting

Model - RVL150



Performance - High airflow 150 CFM, low sound 1.2 sone

LED - Adjustable 2700/3000/3500 /4000/5000K, 1000L, dimmable

ReVent with Humidity Sensing

Model - RVSH150



Performance - High airflow 150 CFM, low sound 1.3 sone

Humidity - Automatically turns fan on when moisture is present and off when dry 📆

Min/Hour Timer - Can be set 0-60 minutes, runs fan for set time every hour 🚳

ReVent with LED Lighting and Humidity Sensing

Model - RVLH150



Performance - High airflow 150 CFM, low sound 1.2 sone

LED - Adjustable 2700/3000/3500 /4000/5000K, 1000L, dimmable

Humidity - Automatically turns fan on when moisture is present and off when dry (54)

Min/Hour Timer - Can be set 0-60 minutes, runs fan for set time every hour 😥

S	Models	RVS150, RVL150, RVSH150, RVLH150
Z	Exhaust Diameter	6 in (15.24 cm)
	Voltage (volts)	120V
0	Frequency (hertz)	60Hz
-	Power (watts)	37.5W
⋖	Air Flow at 0.1 CW	150 CFM
C	Noise (sones)	1.3 Sone (non-lighting), 1.2 Sone (lighting)
ш.	Shield Size	13 ³ / ₈ " x 13 ³ / ₈ " in (34 x 34 cm)
	Opening Length	10 ¹ / ₂ " in (26.7 cm)
C	Opening Width	10 ¹ / ₂ " in (26.7 cm)
ш	Housing Length	10 ¹ / ₂ " in (26.7 cm)
ட	Housing Width	10 ¹ /2" in (26.7 cm)
S	Housing Depth	6 ³ / ₄ " in (17.1 cm)

Product of GTR Technologies Inc. All rights reserved USA and International Patents and Patents Pending See Patents at www.ReVentfans.com

May be used











LIGHTING MODELS						
Models	RVL150, RVLH150					
Brightness (lumens)	1000L at 4000K					
Color Temp (kelvin)	2700, 3000, 3500, 4000, or 5000K					
Power (watts)	13W					

performance at 6" ducting								
Static Pressure (in wg)	Airflow (cfm)	Sound (sones)	Energy (watts)	Duct Size				
RVS150, RVSH150								
0.1	150	1.3	37.5	6 in				
0.25	116		36.7	6 in				
RVL150, RVLH150								
0.1	150	1.2	37.5	6 in				
0.25	111		36.7	6 in				

030624



DETAILED DIMENSIONS

